ABSTRACT OF COST CIVIL WORK PHASE-I (170 Flat Type-B) PROJECT:-SAMAJWADI AWAS YOYNA-Meerut

SI. No.	Schedule Item No.	Description of Work	Unit	Qty.	Rate in Rs.	Amount in Rs.
Α.	SCH P.W.			~.7		
		EARTH WORKS				
1	251	Excavation in foundations in Ordinary Soil (Loam Clay or sand)				
		including lift upto 1.5m. (5 fts.) and lead upto 30 m. (100 fts.) $\&$				
		including filling, watering and ramming of excavated Earth into				
		the trenches or into the Space between the building and sides of				
		foundation trenches or into the space between the building and				
		the sides of foundation trenches or into the plinth and removal				
		and disposal of surplus earth as directed by the engineer-				
		incharges upto a distance of 30m. (100fts.) from the foundation				
		trenches.	Cum	1546.05	63.00	
2		Sand filling in plinth including Supply of necessary quantity of				
		sand from a distance not exceeding 8 km. (5 miles) from the site				
		of work and including watering, ramming, dressing etc. rate to				
		include cost of all materials, labour and T & P etc. required for				
		proper completion of the work.	Cum	191.36	350.00	
		CONCRETE WORKS				
3		Providing & Laying Cement concrete 1:4:8 (1 cement :4 coarse				
		sand : 8 graded stone ballast 40mm. Nominal size.) including				
		supply of all materials, labour and T & P etc. required for proper				
		completion of the work and curing complete, also including cost				
		of formwork in foundation and floors.				
			Cum	127.57	4050.00	
		REINFORCED CEMENT CONCRETE WORK				
4	283	R.C.C work with cement approved coarse sand and 2 cm. (3/4")				
		gauge approved stone grit in the proportion of 1:1.5:3 in lintels				
		of doors and windows excluding supply of reinforcement and its				
		binding but including its fixing and binding the same with 24				
		B.W.G.I binding wire and including necessary centering and				
		shuttering etc. and also including supply of all materials ,labour				
		and T & P etc. required for proper completion of work. Binding				
		wire of supplied by the contractor free of cost.				
		First Floor	Cum	4.120	6300.00	
		2nd Floor	Cum	4.120	6331.50	
		3rd Floor	Cum	4.120	6363.16	
		4th Floor	Cum	4.120	6394.97	
		5th Floor	Cum	4.120	6426.95	
		6th Floor	Cum	4.120	6459.08	
		7th Floor	Cum	4.120	6491.38	
		8th Floor	Cum	4.120	6523.84	
		9th Floor	Cum	4.120	6556.45	
		10th Floor	Cum	4.120	6589.24	
		Total (Qty. and Amount)	Cum	41.20	-	
		BRICK WORK				
5		As in item 303 above but in superstructure including necessary				
-		cutting & moulding of bricks as required thickness of wall not to				
	`	be less than 1 brick .Add extra labour to above items.				
		Stilt	Cum	28.96	4030.00	
		First Floor	Cum	28.96	4050.15	
		2nd Floor	Cum	28.96	4070.40	
		3rd Floor	Cum	28.96	4090.75	
		4th Floor	Cum	28.96	4111.21	
		5th Floor	Cum	28.96	4131.76	
		6th Floor	Cum	28.96	4152.42	
		7th Floor	Cum	28.96	4173.18	
		8th Floor	Cum	28.96	4194.05	
		9th Floor	Cum	28.96	4215.02	
			Cum	28.96	4236.09	

SI. No.	Schedule Item No.	Description of Work	Unit	Qty.	Rate in Rs.	Amount in Rs.
-		Terrrace Floor	Cum	113.01	4257.28	
		Total (Qty. and Amount)	Cum	431.57		
6	305a+30	As in item 305(a) but for walls of Half brick thick in 1:4 cement &	•••••			
0		coarse sand mortar.				
		First Floor	Cum	230.11	4565.00	
		2nd Floor	Cum	230.11	4587.83	
		3rd Floor	Cum	230.11	4610.76	
		4th Floor	Cum	230.11	4633.82	
		5th Floor	Cum	230.11	4656.99	
		6th Floor	Cum	230.11	4680.27	
		7th Floor	Cum	230.11	4703.67	
		8th Floor	Cum	230.11	4703.07	
		9th Floor	Cum	230.11	4750.83	
		10th Floor	Cum	230.11	4774.58	
			Cum	2301.11	4774.58	
		Total (Qty. and Amount)	Cum	2301.11		
-	502	MILD STEEL AND IRON WORK				
7	502	M.S. or Iron work of small size and section such as holding down				
		bolts, hold fast, tie rod, grating etc. wrought to required from				
		including supply of steel ,bolts ,nuts wastage etc and thair fixing required for proper completion of the work				
	E02(a)	Same as in item 502 above but in M. S. Grills & stair case railing				
	502(a)	Stilt Floor	Qtl.	1.20	6100.00	
			Qtl.	11.20	6130.50	
		First Floor	Qtl.	11.27	6161.15	
		2nd Floor 3rd Floor	Qtl.	11.27	6191.96	
			Qtl.	11.27	6222.92	
		4th Floor	Qtl. Qtl.	11.27	6254.03	
		5th Floor	Qti. Qtl.	11.27		
		6th Floor	-	11.27	6285.30	
		7th Floor	Qtl.		6316.73	
		8th Floor	Qtl.	11.27	6348.31	
		9th Floor	Qtl.	11.27	6380.05	
		10th Floor	Qtl.	11.27 113.86	6411.95	
		Total (Qty. and Amount)	Qtl.	115.00		
8	504	Mild Steel (tor steel or plain) in plain work such as R.C.C or R.B				
		Work including bending for proper shape and including supply of				
		steel & its wastage, bend, hooks, and authorised overlapping				
		shall be measured and including cost of binding wire.				
			Otl.	8561.12	5900.00	
			Qtl.	8561.12	5900.00	
			Qtl.	8561.12	5900.00	
٩	New	FLOORING & DADO WORK	Qtl.	8561.12	5900.00	
9	New	FLOORING & DADO WORK Supply & fixing of Kota stone in flooring 20mm thick and joint	Qtl.	8561.12	5900.00	
9	New Item 1	FLOORING & DADO WORK Supply & fixing of Kota stone in flooring 20mm thick and joint filled with 1:2 cement and coarse sand with approved colouring	Qtl.	8561.12	5900.00	
9		FLOORING & DADO WORK Supply & fixing of Kota stone in flooring 20mm thick and joint filled with 1:2 cement and coarse sand with approved colouring materials to be given an even shade with 12mm base coat	Qtl.	8561.12	5900.00	
9		FLOORING & DADO WORK Supply & fixing of Kota stone in flooring 20mm thick and joint filled with 1:2 cement and coarse sand with approved colouring materials to be given an even shade with 12mm base coat (bedding) of 1:2 cement & coarse sand mortar and polished by	Qtl.	8561.12	5900.00	
9		FLOORING & DADO WORK Supply & fixing of Kota stone in flooring 20mm thick and joint filled with 1:2 cement and coarse sand with approved colouring materials to be given an even shade with 12mm base coat (bedding) of 1:2 cement & coarse sand mortar and polished by hand or machine and finally finished with french manson polish	Qtl.	8561.12	5900.00	
9		FLOORING & DADO WORK Supply & fixing of Kota stone in flooring 20mm thick and joint filled with 1:2 cement and coarse sand with approved colouring materials to be given an even shade with 12mm base coat (bedding) of 1:2 cement & coarse sand mortar and polished by hand or machine and finally finished with french manson polish or other approved polish including supply of all materials, labour,	Qtl.	8561.12	5900.00	
9		FLOORING & DADO WORK Supply & fixing of Kota stone in flooring 20mm thick and joint filled with 1:2 cement and coarse sand with approved colouring materials to be given an even shade with 12mm base coat (bedding) of 1:2 cement & coarse sand mortar and polished by hand or machine and finally finished with french manson polish	Qtl.	8561.12	5900.00	
9		FLOORING & DADO WORK Supply & fixing of Kota stone in flooring 20mm thick and joint filled with 1:2 cement and coarse sand with approved colouring materials to be given an even shade with 12mm base coat (bedding) of 1:2 cement & coarse sand mortar and polished by hand or machine and finally finished with french manson polish or other approved polish including supply of all materials, labour,	Qtl.	8561.12	5900.00	
9		FLOORING & DADO WORK Supply & fixing of Kota stone in flooring 20mm thick and joint filled with 1:2 cement and coarse sand with approved colouring materials to be given an even shade with 12mm base coat (bedding) of 1:2 cement & coarse sand mortar and polished by hand or machine and finally finished with french manson polish or other approved polish including supply of all materials, labour, Tools & plants etc. required for proper completion of the work. Stilt Floor	sqm		850.00	
9		FLOORING & DADO WORK Supply & fixing of Kota stone in flooring 20mm thick and joint filled with 1:2 cement and coarse sand with approved colouring materials to be given an even shade with 12mm base coat (bedding) of 1:2 cement & coarse sand mortar and polished by hand or machine and finally finished with french manson polish or other approved polish including supply of all materials, labour, Tools & plants etc. required for proper completion of the work. Stilt Floor First Floor	sqm sqm	1252.37	850.00 854.25	
9		FLOORING & DADO WORK Supply & fixing of Kota stone in flooring 20mm thick and joint filled with 1:2 cement and coarse sand with approved colouring materials to be given an even shade with 12mm base coat (bedding) of 1:2 cement & coarse sand mortar and polished by hand or machine and finally finished with french manson polish or other approved polish including supply of all materials, labour, Tools & plants etc. required for proper completion of the work. Stilt Floor First Floor 2nd Floor	sqm sqm sqm	1252.37 204.42 204.42	850.00 854.25 858.52	
9		FLOORING & DADO WORK Supply & fixing of Kota stone in flooring 20mm thick and joint filled with 1:2 cement and coarse sand with approved colouring materials to be given an even shade with 12mm base coat (bedding) of 1:2 cement & coarse sand mortar and polished by hand or machine and finally finished with french manson polish or other approved polish including supply of all materials, labour, Tools & plants etc. required for proper completion of the work. Stilt Floor First Floor 2nd Floor 3rd Floor	sqm sqm sqm sqm	1252.37 204.42 204.42 204.42	850.00 854.25 858.52 862.81	
9		FLOORING & DADO WORK Supply & fixing of Kota stone in flooring 20mm thick and joint filled with 1:2 cement and coarse sand with approved colouring materials to be given an even shade with 12mm base coat (bedding) of 1:2 cement & coarse sand mortar and polished by hand or machine and finally finished with french manson polish or other approved polish including supply of all materials, labour, Tools & plants etc. required for proper completion of the work. Stilt Floor First Floor 2nd Floor 3rd Floor 4th Floor	sqm sqm sqm sqm sqm	1252.37 204.42 204.42 204.42 204.42	850.00 854.25 858.52 862.81 867.13	
9		FLOORING & DADO WORK Supply & fixing of Kota stone in flooring 20mm thick and joint filled with 1:2 cement and coarse sand with approved colouring materials to be given an even shade with 12mm base coat (bedding) of 1:2 cement & coarse sand mortar and polished by hand or machine and finally finished with french manson polish or other approved polish including supply of all materials, labour, Tools & plants etc. required for proper completion of the work. Stilt Floor First Floor 2nd Floor 3rd Floor 4th Floor 5th Floor	sqm sqm sqm sqm sqm sqm sqm	1252.37 204.42 204.42 204.42 204.42 204.42 204.42	850.00 854.25 858.52 862.81 867.13 871.46	
9		FLOORING & DADO WORK Supply & fixing of Kota stone in flooring 20mm thick and joint filled with 1:2 cement and coarse sand with approved colouring materials to be given an even shade with 12mm base coat (bedding) of 1:2 cement & coarse sand mortar and polished by hand or machine and finally finished with french manson polish or other approved polish including supply of all materials, labour, Tools & plants etc. required for proper completion of the work. Stilt Floor First Floor 2nd Floor 3rd Floor 4th Floor 5th Floor	sqm sqm sqm sqm sqm sqm sqm sqm	1252.37 204.42 204.42 204.42 204.42 204.42 204.42 204.42	850.00 854.25 858.52 862.81 867.13 871.46 875.82	
9		FLOORING & DADO WORK Supply & fixing of Kota stone in flooring 20mm thick and joint filled with 1:2 cement and coarse sand with approved colouring materials to be given an even shade with 12mm base coat (bedding) of 1:2 cement & coarse sand mortar and polished by hand or machine and finally finished with french manson polish or other approved polish including supply of all materials, labour, Tools & plants etc. required for proper completion of the work. Stilt Floor First Floor 2nd Floor 3rd Floor 5th Floor 6th Floor 7th Floor	sqm sqm sqm sqm sqm sqm sqm sqm sqm	1252.37 204.42 204.42 204.42 204.42 204.42 204.42 204.42 204.42	850.00 854.25 858.52 862.81 867.13 871.46 875.82 880.20	
9		FLOORING & DADO WORK Supply & fixing of Kota stone in flooring 20mm thick and joint filled with 1:2 cement and coarse sand with approved colouring materials to be given an even shade with 12mm base coat (bedding) of 1:2 cement & coarse sand mortar and polished by hand or machine and finally finished with french manson polish or other approved polish including supply of all materials, labour, Tools & plants etc. required for proper completion of the work. Stilt Floor First Floor 2nd Floor 3rd Floor 4th Floor 5th Floor	sqm sqm sqm sqm sqm sqm sqm sqm	1252.37 204.42 204.42 204.42 204.42 204.42 204.42 204.42	850.00 854.25 858.52 862.81 867.13 871.46 875.82	

SI. No.	Schedule Item No.	Description of Work	Unit	Qty.	Rate in Rs.	Amount in Rs.
		Total (Qty. and Amount)	Sqm	3296.54		
10	New	Supplying and fixing 6 to 8mm thick ivory or light shades vitrefied				
	Item 4	tiles 600x600mm size in flooring and skirting with 1:3 approved				
		cement and coarse sand morter finished with in its cement				
		colour slurry, jointing and polished of approved quality complete				
		, including supply of all materials, labour, tools and plants etc.				
		required for completion of the work. as per direction of Engineer-				
		in-charge.				
		First Floor	sqm	272.34	1400.00	
		2nd Floor	sqm	272.34	1407.00	
		3rd Floor	sqm	272.34	1414.04	
		4th Floor	sqm	272.34	1421.11	
		5th Floor	sqm	272.34	1428.21	
		6th Floor	sqm	272.34	1435.35	
		7th Floor	sqm	272.34	1442.53	
		8th Floor	sqm	272.34	1449.74	
		9th Floor	sqm	272.34	1456.99	
		10th Floor	sqm	272.34	1464.27	
		Total (Qty. and Amount)	sqm	2723.40		
	/ >	FINISHING WORK				
11	582 (a)	12 mm thick Plaster with cement mortar and coarse sand 1.25-				
		1.75 fineness modules in 1:3 over brick work minimum thickness				
		not to be less than 1 cm. including supply of all materials, labour,				
		tools & plants etc. required for proper completion of the work.				
		First Floor	Sqm	1567.40	140.00	
		2nd Floor	Sqm	1567.40	140.70	
		3rd Floor	Sqm	1567.40	141.40	
		4th Floor	Sqm	1567.40	142.11	
		5th Floor	Sqm	1567.40	142.82	
		6th Floor	Sqm	1567.40	143.54	
		7th Floor	Sqm	1567.40	144.25	
		8th Floor	Sqm	1567.40	144.97	
		9th Floor	Sqm	1567.40	145.70	
		10th Floor	Sqm	1567.40	146.43	
		Terrace	Sqm	604.36	147.16	
		Total (Qty. and Amount)	Sqm	16278.41		
12		12 mm thick Plaster with cement mortar and coarse sand 1.25-				
		1.75 fineness modules in 1:6 over brick work minimum thickness				
	302.300	not to be less than 1 cm. including supply of all materials, labour,				
		tools & plants etc. required for proper completion of the work.				
		tools a plants etc. required for proper completion of the work				
		First Floor	Sqm	3862.15	115.00	
		2nd Floor	Sqm	3862.15	115.58	
		3rd Floor	Sqm	3862.15	116.15	
		4th Floor	Sqm	3862.15	116.73	
		5th Floor	Sqm	3862.15	117.32	
		6th Floor	Sqm	3862.15	117.90	
		7th Floor	Sqm	3862.15	118.49	
		8th Floor	Sqm	3862.15	119.09	
		9th Floor	Sqm	3862.15	119.68	
		10th Floor	Sqm	3862.15	120.28	
		Total (Qty. and Amount)	Sqm	38621.47		
13	596	Add for extra labour and material for plaster over rough face of				
		one brick wall				
		Stilt Floor	sqm	125.91	12.00	
		First Floor	sqm	125.91	12.06	
		2nd Floor	sqm	125.91	12.12	
		3rd Floor	sqm	125.91	12.18	
		4th Floor	sqm	125.91	12.24	

SI. No.	Schedule Item No.	Description of Work	Unit	Qty.	Rate in Rs.	Amount in Rs.
	item ito.	6th Floor	sqm	125.91	12.36	Anount in his.
		7th Floor	sqm	125.91	12.30	
		8th Floor	sqm	125.91	12.49	
		9th Floor	sqm	125.91	12.45	
		10th Floor	sqm	125.91	12.55	
		Terrace	sqm	491.35	12.68	
			Sqm	1876.39	12.08	
14	599	Total (Qty. and Amount) Providing and mixing approved water proofing materials in cement mortar for plastering or in concrete work in the proportion recommended by the manufacturers.	3411	1870.39		
		First Floor	Per Ltr.	14.30	115.00	
		2nd Floor	Per Ltr.	14.30	115.58	
		3rd Floor	Per Ltr.	14.30	116.15	
		4th Floor	Per Ltr.	14.30	116.73	
		5th Floor	Per Ltr.	14.30	117.32	
		6th Floor	Per Ltr.	14.30	117.90	
		7th Floor	Per Ltr.	14.30	118.49	
		8th Floor	Per Ltr.	14.30	119.09	
		9th Floor	Per Ltr.	14.30	119.68	
		10th Floor	Per Ltr.	14.30	120.28	
		Total (Qty. and Amount)	Per Ltr.	142.98		
15	600	Making drip coarse in sun shades or facia with 1:3 cement and fine sand mortar as per direction of engineer-in-charge including supply of all materials, labour, tools & plants etc. required for proper completion of the work.	DeeDM	44.00	20.00	
		First Floor	Per R.M	41.99	20.00	
		2nd Floor	Per R.M	41.99	20.10	
		3rd Floor	Per R.M	41.99	20.20	
		4th Floor	Per R.M	41.99	20.30	
		5th Floor	Per R.M	41.99	20.40	
		6th Floor	Per R.M	41.99	20.51	
		7th Floor	Per R.M	41.99	20.61	
		8th Floor	Per R.M	41.99	20.71	
		9th Floor	Per R.M	41.99	20.81	
		10th Floor	Per R.M	41.99	20.92	
		Total (Qty. and Amount)	Per R.M	419.90		
16	0-51050	Distempering (first coat) with oil bound distemper of approved brand and manufacture and of required shade of undecorated wall surface to give an even shade over and including a priming coat with cement primer of approved brand and manufacture such as Berger,J&N, Shalimar, Asian Paint after throughly brushing the surface free from mortar dropping and other foreign matters and also including the surface even with plaster of Paris or approved synthetic materials and sand papered smooth including supply of all materials, labour, Tools & plants etc. required for proper competion of the work.				
		As in item (649) above but for every coat after the first coat.				
		Stilt	Sqm	1252.37	60.00	
		First Floor	Sqm	2626.13	60.30	
		2nd Floor	Sqm	2626.13	60.60	
		3rd Floor	Sqm	2626.13	60.90	
		4th Floor	Sqm	2626.13	61.21	
		5th Floor	Sqm	2626.13	61.52	
		6th Floor	Sqm	2626.13	61.82	
		7th Floor	Sqm	2626.13	62.13	
		8th Floor	Sqm	2626.13	62.44	
		9th Floor	Sqm	2626.13	62.75	
		10th Floor	Sqm	2626.13	63.07	
	-		~ ~			

SI. No.	Schedule Item No.	Description of Work	Unit	Qty.	Rate in Rs.	Amount in Rs.
17	660+Ne	Finishing wall with Exterior Acrylic Emulsion 'Weathercoat' or				
	w Item	Apex of approved make and quality on new work with 3 coats to				
	1&2	give an even shade including a coat of primer, putty & supply of				
		all materials, labour, tools and plants etc. required for proper				
		completion of work				
		First Floor	Sq m	1580.82	108.00	
		2nd Floor	Sqm	1580.82	108.54	
		3rd Floor	Sq m	1580.82	108.34	
			Sq m	1580.82	109.63	
		4th Floor		1580.82		
		5th Floor	Sq m	1580.82	110.18	
		6th Floor	Sq m	1580.82	110.73	
		7th Floor	Sq m		111.28	
		8th Floor	Sq m	1580.82	111.84	
		9th Floor	Sq m	1580.82	112.40	
		10th Floor	Sq m	1580.82	112.96	
		Total (Qty. and Amount)	Sq m	15808.19		
18	9.96	Providing and fixing aluminium sliding door bolts, ISI marked				
		anodised (anodic coating not less than grade AC 10 as per IS :				
		1868), transparent or dyed to required colour or shade, with nuts				
		and screws etc. complete :				
	9.96.1	300x16 mm				
		First Floor	each	136.00	219.00	
		2nd Floor	each	136.00	220.10	
		3rd Floor	each	136.00	221.20	
		4th Floor	each	136.00	222.30	
		5th Floor	each	136.00	223.41	
		6th Floor	each	136.00	224.53	
		7th Floor	each	136.00	225.65	
		8th Floor	each	136.00	226.78	
		9th Floor	each	136.00	227.91	
		10th Floor	each	136.00	229.05	
		Total (Qty. and Amount)	each	1360.00	225.05	
19	9.97	Providing and fixing aluminium tower bolts ISI marked anodised	cacin	1300.00		
19	5.57	(anodic coating not less than grade AC 10 as per IS : 1868)				
		transparent or dyed to required colour or shade with necessary screws etc. complete :				
i	0.07.1					
1	9.97.1	300x10 mm	oach	136.00	107.20	
		First Floor	each		107.20	
		2nd Floor	each	136.00	107.74	
		3rd Floor	each	136.00	108.27	
		4th Floor	each	136.00	108.82	
		5th Floor	each	136.00	109.36	
		6th Floor	each	136.00	109.91	
		7th Floor	each	136.00	110.46	
		8th Floor	each	136.00	111.01	
		9th Floor	each	136.00	111.56	
		10th Floor	each	136.00	112.12	
		Total (Qty. and Amount)	each	1360.00		
20	9.1	Providing and fixing aluminium handles of approved make				
20	5.1	anodized (anodic coating not less than grade AC 10 as per IS :				
		1868) transparent or dyed to required colour or shade with				
		necessry screws etc. complete.				
i	9.100.1	125 mm				
	5.100.1		oach	240.00	66.75	
		First Floor	each	340.00	66.75	
		2nd Floor	each	340.00	67.08	
		3rd Floor	each	340.00	67.42	
		4th Floor	each	340.00	67.76	
		5th Floor	each	340.00	68.10	
		6th Floor	each	340.00	68.44	
		7th Floor	each	340.00	68.78	
		8th Floor	each	340.00	69.12	
			each each	340.00 340.00	69.12 69.47	

SI. No.	Schedule Item No.	Description of Work	Unit	Qty.	Rate in Rs.	Amount in Rs.
		Total (Qty. and Amount)	each	3400.00		
		MISCELLANEOUS				
21	19.02	Providing and injecting chemical for preconstruction antitermite		1		
		treatment and creating and chemical barrier under and arround				
		the column pits wall trenches basement excavation top surface				
		in plinth filling junction of wall and floor, along the external per				
		meter of binding expansion joints surrounding or pipes and				
		conduit etc. complete (plinth area of the building at ground floor only shall be measured as per I.S 6313 (part II 1981) Aldrine				
		, , , , ,				
		emulsifiable concentrate or any other approved material such as				
		heptachlor of chlordane will be used. The rate of application of				
		chemical emulsion shall be as follows:-				
			sqm	1252.37	110.00	
		1. Treatment for massonary and foundation 5 litres per sqm.	•			
		2.Backfill in immediate contact with foundation 7.5 litres per				
		sqm.				
		3. Treatment of surface of plinth filling 5 litres per sqm				
		4. Treatment of soil along external parameter of Building				
		с				
		7.5 litres per sqm.				
		5. Treatment of soil under external parameter 5 litres per sqm.				
22	NEW	Providing & Laying "brick coba " average 12 cm thick laid with				
		M150 class brick bat coba 7.50 cm thick with gap of 15 mm to				
	(CHAPTE	each other over 20 mm thick base of cement mortar 1:4 cement				
	•	and coarse sand mixed with water proofing compound in 1:4				
		cement and coarse sand mortar finished smooth top mashed				
		false square 30cm *30 cm and said wall perapet shall be				
		monolithic plaster wall upto 30 cm higher and junction and				
		corner shall be rounded by cement and coarse sand masonry.				
		Coba with top finished plaster mixed with acetic water proofing				
		compound @ 2% by weight &including S/O all material ,labour				
		T&P etc complete for proper completion of work.				
			Sq m	1252.37	800.00	
		SCH P.W.D SUB- HEAD TOTAL:S.NO. (1-22)				
3.	DSR-2014	CONCRETE WORKS				
23	4.17	Making plinth protection 50mm thick of cement concrete 1:3:6 (1				
-5		cement :3 coarse sand : 6graded stone aggregate 20mm nominal				
		size) over 75mm bed by dry brick ballast 40mm nominal size well				
		rammed and consolidated and grouted with fine sand including				
		finishing the top smooth	Cauna	204.01	4055L	
			Sqm.	294.81	#REF!	
24	4.2 New	Providing and laying cement concrete in retaining walls, return				
		walls, walls (any thickness) including attached pilasters, columns,				
		piers, abutments, pillars, posts, struts, buttresses, string or lacing				
		courses, parapets, coping, bed blocks, anchor blocks, plain				
		window sills fillets surplus flass ats we to flass five level				
		window sills, fillets, sunken floor,etc., up to floor five level,				
		including the cost of centering, shuttering and finishing :				
	4.2.2		Cum	99.26	#REF!	

SI. No.	Schedule Item No.	Description of Work	Unit	Qty.	Rate in Rs.	Amount in Rs.
25	5.44	Providing and fixing of expansion joint system related with floor				
		location as per drawings and direction of Engineer-In-Charge. The				
		joints system will be of extruded aluminum base members, self				
		aligning / self centering arrangement and support plates etc. as				
		per ASTM B221-02. The system shall be such that it provides				
		floor to floor /floor to wall expansion control system for various				
		vertical localtion in load application areas that accommodates				
		multi directional seismic movement without stress to it's				
		components. System shall consist of metal profiles with a				
		universal aluminum base member designed to accommodate				
		various project conditions and finish floor treatments. The cover				
		plate shall be designed of width and thickness required to satisfy				
		projects movement and loading requirements and secured to				
		base members by utilizing manufacturer's pre-engineered self-				
		centering arrangement that freely rotates / moves in all				
		directions. The Self – centering arrangement shall exhibit circular				
		sphere ends that lock and slide inside the corresponding				
		aluminum extrusion cavity to allow freedom of movement and				
		flexure in all directions including vertical displacement.				
		Dravician of Maistura Parriar Mambrana in the Joint System to				
		Provision of Moisture Barrier Membrane in the Joint System to have watertight joint is mandatory requirement all as per the				
		manufactures design and as approved by Engineer -in- Charge .				
		(Material shall confirm to ASTM 6063.)				
i	5.44.1	Floor Joint of 100 mm gap				
		Stilt	rm	9.63	#REF!	
		First Floor	rm	9.63	#REF!	
		2nd Floor	rm	9.63	#REF!	
		3rd Floor	rm	9.63	#REF!	
		4th Floor	rm	9.63	#REF!	
		5th Floor	rm	9.63	#REF!	
		6th Floor	rm	9.63	#REF!	
		7th Floor	rm	9.63	#REF!	
		8th Floor	rm	9.63	#REF!	
		9th Floor	rm	9.63	#REF!	
		10th Floor	rm	9.63	#REF!	
		Total (Qty. and Amount)	rm	105.93		
26	5.45	Providing and fixing of expansion joint system related with wall				
		joint (internal/ external) location as per drawings and direction of				
		Engineer-In- Charge. The joints shall be of extruded aluminum				
		base members, self aligning / centering arrangement and support				
		plates as per ASTM B221- 02. The material shall be such that it				
		provides an Expansion Joints System suitable for vertical wall to				
		wall/ wall to corner application, both new and existing				
		construction in office Buildings & complexes with no slipping				
		down tendency amongst the components of the Joint System.				
		The Joint System shall utilize light weight aluminum profiles				
		exhibiting minimal exposed aluminum surfaces mechanically				
		snap locking the multicellular to facilitate movement. (Material				
		shall confirm to ASTM 6063.)				
i	5.45.1	Wall Joint of 100 mm gap				
		Stilt	rm	5.97	#REF!	
		First Floor	rm	5.97	#REF!	
		2nd Floor	rm	5.97	#REF!	
		3rd Floor	rm	5.97	#REF!	
		4th Floor	rm	5.97	#REF!	
		5th Floor	rm	5.97	#REF!	
		6th Floor	rm	5.97	#REF!	
		7th Floor	rm	5.97	#REF!	
		8th Floor	rm	5.97	#REF!	
		9th Floor	rm	5.97	#REF!	

SI. No.	Schedule Item No.	Description of Work	Unit	Qty.	Rate in Rs.	Amount in Rs.
140.	item ivo.	10th Floor	rm	5.97	#REF!	Amount in N3.
		Total (Qty. and Amount)	rm	65.70		
27	5.46	Providing and fixing of expansion joint system of approved make				
		and manufactures for various roof locations as per approved				
		drawings and direction of Engineer-In-Charge. The joints shall be				
		of extruded aluminum base members with, self aligning and self				
		centering arragement support plates asper ASTM B221-02. The				
		system shall be such that it provides watertight roof to roof/roof				
		to corner joint cover expansion control system that is capable of				
		accommodating multidirectional seismic movement without				
		stress to its components. System shall consist of metal profile				
		that incorporates a universal aluminum base member designed				
		to accommodate various project conditions and roof treatments.				
		The coverplate shall be designed of width and thickness required				
		to satisfy movement and loading requirements and secured to				
		base members by utilizing manufacturer's pre-engineered self-				
		centering arrangement that freely rotates / moves in all				
		directions. The Self centering arrangement shall exhibit circular				
		sphere ends that lock and slide inside the corresponding				
		aluminum extrusion cavity to allow freedom of movement and				
		flexure in all directions including vertical displacement.				
					#REF!	
		The Joint System shall resists damage or deterioration from the			TINEI';	
		impact of falling ice, exposure to UV, airborne contaminants and				
		occasional foot traffic from maintenance personnel. Provision of				
		Moisture Barrier Membrane in the Joint System to have water				
		tight joint is mandatory requirement. Material shall confirm to				
		ASTM 6063.				
i	5.46.1	Roof Joint of 100 mm gap	rm	9.63	#REF!	
		MARBLE & GRANITE WORK				
28	8.2	Providing and fixing 18mm thick gang saw cut (premoulded and				
		prepolished) machine cut for kitchen platforms, vanity counters,				
		window sills , facias and similar locations of required size of				
		approved shade, colour and texture laid over 20mm thick base				
		cement mortar 1:4 (1 cement : 4 coarse sand) with joints treated				
		with white cement, mixed with matching pigment, epoxy touch				
		ups, including rubbing, curing, moulding and polishing to edge to				
		give high gloss finish etc. complete at all levels.				
	8.2.1	Udaipur green marble				
	8.2.1.2	Area of slab over 0.50 Sqm.(For Counter)		10.10		
		First Floor	Sqm.	40.46	#REF!	
		2nd Floor	Sqm.	40.46	#REF!	
		3rd Floor	Sqm.	40.46	#REF!	
	<u> </u>	4th Floor	Sqm.	40.46	#REF!	
		5th Floor	Sqm.	40.46	#REF!	
		6th Floor	Sqm.	40.46	#REF!	
		7th Floor	Sqm.	40.46	#REF!	
	ļ	8th Floor	Sqm.	40.46	#REF!	
		9th Floor	Sqm.	40.46	#REF!	
		10th Floor	Sqm.	40.46	#REF!	
		Total (Qty. and Amount)	Sq m	404.60		
29	8.3.	Providing edge moulding to 18 mm thick marble stone counters,				
		Vanities etc., including machine polishing to edge to give high				
		gloss finish etc. complete as per design approved by Engineer-in-				
		Charge.				
	8.3.1	Marble work				
		First Floor	rm	57.29	#REF!	
		2nd Floor	rm	57.29	#REF!	
		3rd Floor	rm	57.29	#REF!	

SI.	Schedule					
No.	Item No.	Description of Work	Unit	Qty.	Rate in Rs.	Amount in Rs.
		5th Floor	rm	57.29	#REF!	
		6th Floor	rm	57.29	#REF!	
		7th Floor	rm	57.29	#REF!	
		8th Floor	rm	57.29	#REF!	
		9th Floor	rm	57.29	#REF!	
		10th Floor	rm	57.29	#REF!	
		Total (Qty. and Amount)	rm	572.90		
30	8.5	Extra for providing opening of required size & shape for wash				
		basins/ kitchen sink in kitchen platform, vanity counters and				
		similar location in marble/Granite/Stone work including				
		necessary holes for pillar taps etc. including rubbing and				
		polishing of cut edge etc. complete.				
				47.00		
		First Floor	each	17.00	#REF!	
		2nd Floor	each	17.00	#REF!	
		3rd Floor	each	17.00	#REF!	
		4th Floor	each	17.00	#REF!	
		5th Floor	each	17.00	#REF!	
		6th Floor	each	17.00	#REF!	
		7th Floor	each	17.00	#REF!	
		8th Floor	each	17.00	#REF!	
		9th Floor	each	17.00	#REF!	
	-	10th Floor	each	17.00	#REF!	
		Total (Qty. and Amount)	each	170.00		
31	8.8	Providing and fixing expansion hold fasteners on C.C.				
51	0.0	/R.C.C./Brick masonry surface backing including drilling necessary				
		holes and the cost of bolt etc complete.				
	8.8.1.3	Fastener with threaded dia 12 mm.				
	0.0.1.5		oach	1122	4055L	
		First Floor	each		#REF!	
		2nd Floor	each	1122	#REF!	
		3rd Floor	each	1122	#REF!	
		4th Floor	each	1122	#REF!	
		5th Floor	each	1122	#REF!	
		6th Floor	each	1122	#REF!	
		7th Floor	each	1122	#REF!	
		8th Floor	each	1122	#REF!	
		9th Floor	each	1122	#REF!	
		10th Floor	each	1122	#REF!	
		Total (Qty. and Amount)	each	11220		
		WOOD & PVC WORK				
32	9.1	Providing wood work in frames of doors, windows, clerestory				
	•	windows and other frames, wrought framed and fixed in position				
		with hold fast lugs or with dash fasteners of required dia &				
		length (hold fast lugs or dash fastener shall be paid for				
	9.1.3	Kiln seasoned and chemically treated hollock wood				
		First Floor	cum	1.81	#REF!	
		2nd Floor	cum	1.81	#REF!	
		3rd Floor	cum	1.81	#REF!	
		4th Floor	cum	1.81	#REF!	
		5th Floor	cum	1.81	#REF!	
		6th Floor	cum	1.81	#REF!	
		7th Floor	cum	1.81	#REF!	
		8th Floor	cum	1.81	#REF!	
		9th Floor	cum	1.81	#REF!	
_		10th Floor	cum	1.81	#REF!	
			cum	1.81 18.14	#NEĽ!	
22	0.0	Total (Qty. and Amount)	culli	10.14	├	
33	9.9	Providing and fixing glazed shutters for doors, windows and				
		clerestory windows using 4 mm thick float glass panes, including				
		ISI marked M.S. pressed butt hinges bright finished of required				
		size with necessary screws.				
	9.9.2	Kiln seasoned and chemically treated hollock wood				
-	9.9.2.2	30 mm thick				

SI.	Schedule					
No.	Item No.	Description of Work	Unit	Qty.	Rate in Rs.	Amount in Rs.
		2nd Floor	Sqm	174.98	#REF!	
		3rd Floor	Sqm	174.98	#REF!	
		4th Floor	Sqm	174.98	#REF!	
		5th Floor	Sqm	174.98	#REF!	
		6th Floor	Sqm	174.98	#REF!	
		7th Floor	Sqm	174.98	#REF!	
		8th Floor	Sqm	174.98	#REF!	
		9th Floor	Sqm	174.98	#REF!	
		10th Floor	Sqm	174.98	#REF!	
		Total (Qty. and Amount)	Sqm	1749.81		
34	9.21	Providing and fixing ISI marked flush door shutters conforming to				
		IS :2202 (Part I) non-decorative type, core of block board				
		construction with frame of 1st class hard wood and well matched				
		commercial 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters:				
	9.21.2	30 mm thick including ISI marked Stainless Steel butt hinges with				
		necessary screws				
		First Floor	Sqm	361.97	#REF!	
		2nd Floor	Sqm	361.97	#REF!	
		3rd Floor	Sqm	361.97	#REF!	
		4th Floor	Sqm	361.97	#REF!	
		5th Floor	Sqm	361.97	#REF!	
		6th Floor	Sqm	361.97	#REF!	
		7th Floor	Sqm	361.97	#REF!	
		8th Floor	Sqm	361.97	#REF!	
		9th Floor	Sqm	361.97	#REF!	
		10th Floor	Sqm	361.97	#REF!	
		Total (Qty. and Amount)	Sqm	3619.73		
35	9.40	Providing and fixing wooden moulded beading to door and				
		window frames with iron screws, plugs and priming coat on unexposed surface etc.complete :50x12 mm 2nd class teak wood				
	9.40.2	Kiln seasoned and chemically treated hollock wood				
	9.40.2.1	50x12 mm				
		First Floor	rm	86.70	#REF!	
		2nd Floor	rm	86.70	#REF!	
		3rd Floor	rm	86.70	#REF!	
		4th Floor	rm	86.70	#REF!	
		5th Floor	rm	86.70	#REF!	
		6th Floor	rm	86.70	#REF!	
		7th Floor	rm	86.70	#REF!	
		8th Floor	rm	86.70	#REF!	
		9th Floor	rm	86.70	#REF!	
		10th Floor	rm	86.70	#REF!	
		Total (Qty. and Amount)	rm	867.00		
36	9.101	Providing and fixing aluminium hanging floor door stopper, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour and shade,				
		with necessary screws etc. complete.				
	9.101.1	Single rubber stopper				
		First Floor	each	136.00	#REF!	
		2nd Floor	each	136.00	#REF!	
		3rd Floor	each	136.00	#REF!	
		4th Floor	each	136.00	#REF!	
		5th Floor	each	136.00	#REF!	
		6th Floor	each	136.00	#REF!	
		7th Floor	each	136.00	#REF!	
		8th Floor	each	136.00	#REF!	
		9th Floor	each	136.00	#REF!	
		10th Floor	each	136.00	#REF!	
		Total (Qty. and Amount)	each	1360.00		

SI. No.	Schedule Item No.	Description of Work	Unit	Qty.	Rate in Rs.	Amount in Rs.
37	10.14	Providing and fixing pressed steel door frames conforming to				
		IS:4351 manufactured from commercial mild steel sheet of 1.6				
		mm thickness including hinges, jamb, lock jamb, bead and if				
		required angle threshold of mild steel angle of section 50x 25				
		mm, or base ties of 1.6mm pressed mild steel welded or rigidly				
		fixed together by mechanical means, adjustable lugs with split				
		end tail to each jamb including steel butt hinges 2.5 mm thick				
		with mortar guards, lock strike-plate and shock absorbers as				
		specified and applying a coat of approved steel primer after pre-				
		treatment of the surface as directed by the Engineer-in-charge.				
	10.14.1	Profile B				
		Fixing with adjustable lugs with split end tail to each jamb				
	10.1 1.1.	First Floor	Sqm	994.50	#REF!	
		2nd Floor	Sqm	994.50	#REF!	
		3rd Floor	Sqm	994.50	#REF!	
			Sqm	994.50	#REF!	
		4th Floor				
		5th Floor	Sqm	994.50	#REF!	
		6th Floor	Sqm	994.50	#REF!	
		7th Floor	Sqm	994.50	#REF!	
		8th Floor	Sqm	994.50	#REF!	
		9th Floor	Sqm	994.50	#REF!	
		10th Floor	Sqm	994.50	#REF!	
		Total (Qty. and Amount)	Sqm	9945.00		
38	14.70	Melamine polishing on wood work (one or more coat).				
		First Floor	Sqm	723.95	#REF!	
		2nd Floor	Sqm	723.95	#REF!	
		3rd Floor	Sqm	723.95	#REF!	
		4th Floor	Sqm	723.95	#REF!	
		5th Floor	Sqm	723.95	#REF!	
				723.95		
		6th Floor	Sqm		#REF!	
		7th Floor	Sqm	723.95	#REF!	
		8th Floor	Sqm	723.95	#REF!	
		9th Floor	Sqm	723.95	#REF!	
		10th Floor	Sqm	723.95	#REF!	
		Total (Qty. and Amount)	Sqm	7239.45		
		FLOORING & DADO WORK				
39	11.27	Kota stone slabs 20 mm thick in risers of steps, skirting, dado and				
		pillars laid on 12 mm (average) thick cement mortar 1:3 (1				
		cement: 3 coarse sand) and jointed with grey cement slurry				
		mixed with pigment to match the shade of the slabs, including				
		rubbing and polishing complete.				
		Stilt	sqm	50.40	#REF!	
		First Floor	sqm	50.40	#REF!	
		2nd Floor	sqm	50.40	#REF!	
		3rd Floor	sqm	50.40	#REF!	
		4th Floor	sqm	50.40	#REF!	
		5th Floor	sqm	50.40	#REF!	
		6th Floor	sqm	50.40	#REF!	
		7th Floor	sqm	50.40	#REF!	
		8th Floor	sqm	50.40	#REF!	
		9th Floor	sqm	50.40	#REF!	
		10th Floor	sqm	50.40	#REF!	
		Total (Qty. and Amount)	sqm	554.40		
40	11.36	Providing and fixing Ist quality ceramic glazed wall tiles				
-		conforming to IS: 15622 (thickness to be specified by the				
		manufacturer), of approved make, in all colours, shades except				
		burgundy, bottle green, black of any size as approved by				
		Engineer-in-Charge, in skirting, risers of steps and dados, over 12				
		mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand)				
		and jointing with grey cement slurry @ 3.3kg per sqm, including				
		and the first of the second				
		pointing in white cement mixed with pigment of matching shade complete				

SI.	Schedule	Description of Work	11-14	01-1	Data in Da	Amount in De
No.	Item No.	Description of Work	Unit	Qty. 643.37	Rate in Rs. #REF!	Amount in Rs.
		First Floor	sqm	643.37	#REF! #REF!	
		2nd Floor	sqm	643.37		
		3rd Floor	sqm	643.37	#REF!	
		4th Floor	sqm		#REF!	
		5th Floor	sqm	643.37	#REF!	
		6th Floor	sqm	643.37	#REF!	
		7th Floor	sqm	643.37	#REF!	
		8th Floor	sqm	643.37	#REF!	
		9th Floor	sqm	643.37	#REF!	
		10th Floor	sqm	643.37	#REF!	
		Total (Qty. and Amount)	sqm	6433.65		
41	11.37	Providing and laying Ceramic glazed floor tiles of size 300x300				
		mm (thickness to be specified by the manufacturer) of 1st quality				
		conforming to IS : 15622 of approved make in colours such as				
		White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement				
		mortar 1:4 (1 Cement : 4 Coarse sand), including pointing the				
		joints with white cement and matching pigment etc., complete.				
		First Floor	sqm	110.86	#REF!	
		2nd Floor	sqm	110.86	#REF!	
		3rd Floor	sqm	110.86	#REF!	
		4th Floor	sqm	110.86	#REF!	
		5th Floor	sqm	110.86	#REF!	
		6th Floor	sqm	110.86	#REF!	
		7th Floor	sqm	110.86	#REF!	
		8th Floor	sqm	110.86	#REF!	
		9th Floor	sqm	110.86	#REF!	
		10th Floor	sqm	110.86	#REF!	
		Total (Qty. and Amount)	sqm	1108.64	#REF .	
42	11.38	Providing and laying Ceramic glazed floor tiles of size 300x300	-	1100.04		
42	11.50	mm (thickness to be specified by the manufacturer), of 1st				
		quality conforming to IS : 15622, of approved make, in all				
		colours, shades, except White, Ivory, Grey, Fume Red Brown, laid				
		on 20 mm thick bed of cement mortar 1:4 (1 Cement : 4 Coarse				
		sand), including pointing the joints with white cement and				
		matching pigments etc., complete.				
		First Floor	sqm	557.77	#REF!	
	-	2nd Floor	sqm	557.77	#REF!	
				557.77		
		3rd Floor	sqm	557.77	#REF!	
		4th Floor	sqm	557.77	#REF!	
		5th Floor	sqm		#REF!	
	-	6th Floor	sqm	557.77	#REF!	
		7th Floor	sqm	557.77	#REF!	
		8th Floor	sqm	557.77	#REF!	
		9th Floor	sqm	557.77	#REF!	
		10th Floor	sqm	557.77	#REF!	
		Total (Qty. and Amount)	sqm	5577.70		
		ROOF & FALSE CEILING WORK				
43	12.22	Making khurras 45x45 cm with average minimum thickness of 5				
		cm cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded				
		stone aggregate of 20 mm nominal size) over P.V.C. sheet				
		1mx1mx400micron, finished with 12mm cement plaster 1:3 (1				
		cement : 3 coarse sand) and a coat of neat cement, rounding the				
		edges and making and finishing the outlet complete.				
			each	16.00	#REF!	
		FINISHING WORK				
44	13.61.1	FINISHING WORK Painting with synthetic enamel paint of approved brand and				
44	13.61.1					
44	13.61.1	Painting with synthetic enamel paint of approved brand and				

SI. No.	Schedule Item No.	Description of Work	Unit	Qty.	Rate in Rs.	Amount in Rs.
		First Floor	Sqm	122.12	#REF!	
		2nd Floor	Sqm	122.12	#REF!	
		3rd Floor	Sqm	122.12	#REF!	
		4th Floor	Sqm	122.12	#REF!	
		5th Floor	Sqm	122.12	#REF!	
		6th Floor	Sqm	122.12	#REF!	
		7th Floor	Sqm	122.12	#REF!	
		8th Floor	Sqm	122.12	#REF!	
		9th Floor	Sqm	122.12	#REF!	
		10th Floor	Sqm	122.12	#REF!	
		Total (Qty. and Amount)	sqm	1242.81		
		SCH DSR S.NO.(23-44) SUB- HEAD TOTAL :	• • •			
c.		EDULE ITEM				
	NON SCH	FINISHING WORK				
45	NC					
45	NSI	Providing and fixing GI hexagonal chicken wire mesh of size 12mm x22g at the junction of disimilar surfaces of brick masonry				
		wall and R C C column by beams and the like including necessary				
		nails for fixing etc, complete all as per specification and direction				
		of Engineer -in -charge for all floor at all heights.				
			C	140 50	400.00	ļ
		Stilt Floor	Sqm	149.58	120.00	L
		First Floor	Sqm	149.58	120.60	
		2nd Floor	Sqm	149.58	121.20	
		3rd Floor	Sqm	149.58	121.81	
		4th Floor	Sqm	149.58	122.42	
		5th Floor	Sqm	149.58	123.03	
		6th Floor	Sqm	149.58	123.65	
		7th Floor	Sqm	149.58	124.26	
		8th Floor	Sqm	149.58	124.88	
		9th Floor	Sqm	149.58	125.51	
		10th Floor	Sqm	149.58	126.14	
		Total (Qty. and Amount)		1645.38		
46	NSI	Providing and laying cinder filling in the toilets complete as				
		directed by engineer in charge				
		First Floor	Cum	34.04	300.00	
		2nd Floor	Cum	34.04	301.50	
		3rd Floor	Cum	34.04	303.01	
		4th Floor	Cum	34.04	304.52	
		5th Floor	Cum	34.04	306.05	
		6th Floor	Cum	34.04	307.58	
		7th Floor	Cum	34.04	309.11	
		8th Floor	Cum	34.04	310.66	
		9th Floor	Cum	34.04	312.21	
		10th Floor	Cum	34.04	313.77	
		Total (Qty. and Amount)		340.43		
47	13.16.1	6 mm cement plaster of mix 1:3 (1 cement: 3 coarse sand) in		-		
77		ceiling.				
		First Floor	sqm	873.05	117.20	
		2nd Floor	sqm	873.05	117.79	
		3rd Floor	sqm	873.05	118.37	
		4th Floor	sqm	873.05	118.97	
		5th Floor	sqm	873.05	119.56	
		6th Floor	sqm	873.05	119.56	ļ
				873.05	120.16	ļ
		7th Floor	sqm			
		8th Floor	sqm	873.05	121.36	
		9th Floor	sqm	873.05	121.97	ļ
		10th Floor	sqm	873.05	122.58	
	1	Total (Qty. and Amount)	sqm	8730.50		

SI. No.	Schedule Item No.	Description of Work	Unit	Qty.	Rate in Rs.	Amount in Rs.
48	NSI	RCC work with M-25 grade of cement concrete approved corse				
		sand and stone grit in Slab excluding supply reinforcement and				
		its binding the but including its fixing and binding the same with				
		25 BWG binding wire and including necessary centering and				
		shuttering etc. and also including supply of all meterial, labour				
		and tools and plant etc. required for proper completion of the				
		works including cost of binding wire.				
		Stilt	Cum	5.40	10036.99	
		First Floor	Cum	154.65	10030.33	
		2nd Floor	Cum	154.65	10137.61	
		3rd Floor	Cum	154.65	10137.01	
		4th Floor	Cum	154.65	10138.30	
		5th Floor	Cum	154.65	10235.24	
		6th Floor	Cum	154.65	10230.43	
		7th Floor	Cum	154.65	10393.59	
		8th Floor	Cum	154.65	10355.55	
		9th Floor	Cum	154.65	10445.30	
		10th Floor	Cum	154.65	10497.79	
		Terrace Floor	Cum	193.31	10530.28	
			Cum	193.31 1745.21	10603.03	
40	NC	Total (Qty. and Amount)	Cum	1745.21		
49	NSI	RCC work with M-25 grade of cement concrete approved corse				
		sand and stone grit in Lighter Beam having span up to 6.00 m				
		excluding supply reinforcement and its binding the but including				
		its fixing and binding the same with 25 BWG binding wire and				
		including necessary centering and shuttering etc. and also				
		including supply of all meterial, labour and tools and plant etc.				
		required for proper completion of the works including cost of				
		binding wire.		100.00		
		Stilt	Cum	129.30	9730.00	
		First Floor	Cum	85.35	9778.65	
		2nd Floor	Cum	85.35	9827.54	
		3rd Floor	Cum	85.35	9876.68	
		4th Floor	Cum	85.35	9926.06	
		5th Floor	Cum	85.35	9975.69	
		6th Floor	Cum	85.35	10025.57	
		7th Floor	Cum	85.35	10075.70	
		8th Floor	Cum	85.35	10126.08	
		9th Floor	Cum	85.35	10176.71	
		10th Floor	Cum	85.35	10227.59	
		Total (Qty. and Amount)	Cum	982.81		
50	NSI	RCC work with M-20 grade of cement concrete approved corse				
		sand and stone grit in Foundation and Footing excluding supply				
		reinforcement and its binding the but including its fixing and				
		binding the same with 25 BWG binding wire and including				
		necessary centering and shuttering etc. and also including supply				
		of all meterial, labour and tools and plant etc. required for				
		proper completion of the works including cost of binding wire.				
			Cum	797.32	6321.00	
51	NSI	RCC work with M-30 grade of cement concrete approved corse				
		sand and stone grit for RCC Column excluding supply				
		reinforcement and its binding the but including its fixing and				
		binding the same with 25 BWG binding wire and including				
		necessary centering and shuttering etc. and also including supply				
		of all meterial, labour and tools and plant etc. required for				
		proper completion of the works including cost of binding wire.				
		Ch.16	C	122.04	10960.00	
		Stilt	Cum	122.04	10860.00	
		First Floor	Cum	119.32	10914.30	
		2nd Floor	Cum	119.32	10968.87	
		3rd Floor	Cum	119.32	11023.72	
		4th Floor	Cum	119.32	11078.83	
		5th Floor	Cum	119.32	11134.23	

SI.	Schedule					
No.	Item No.	Description of Work	Unit	Qty.	Rate in Rs.	Amount in Rs.
		6th Floor	Cum	119.32	11189.90	
		7th Floor	Cum	119.32	11245.85	
		8th Floor	Cum	119.32	11302.08	
		9th Floor	Cum	119.32	11358.59	
		10th Floor	Cum	119.32	11415.38	
		Total (Qty. and Amount)	Cum	1315.27		
		NON SCHEDULE ITEM S.NO.(45-51)				
		TOTAL (A+B+C)				