

SUMMARY OF PRICES FOR PLUMBING WORKS FOR Phase-1,(Block-L&M) Type-C				
S.NO.		DESCRIPTION	AMOUNT (RS)	
			DSR	NON DSR

BILL OF QUANTITIES & ESTIMATE							
S.NO.	(DSR-2014)	DESCRIPTION	UNIT	QTY.	RATE	AMOUNT (RS)	
						DSR	NON DSR
SUBHEAD-I: SANITARY INSTALLATIONS							
1.1	17.78	Providing and fixing white vitreous china extended wall mounting water closet of size 780x370x690 mm of approved shape including providing & fixing white vitreous china cistern with dual flush fitting of flushing capacity 3 litre/6 litre (adjustable to 4 litre/8 litres), including seat cover, and cistern fittings, nuts, bolts and gasket etc complete.	Each	280	9,661.73		
1.2	17.7	Providing and fixing wash basin with CI brackets, 15mm CP brass pillar taps, 32mm CP brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls where ever require.					
	17.7.2	White Vitreous China Wash basin size 630x450mm with a single 15mm CP brass pillar tap.	Each	280	1,922.94		
1.3	17.10	Providing and fixing Salem Stainless Steel A ISI 304 (18/8) kitchen sink as per IS: 13983 with CI brackets and stainless steel waste with plug 40mm including painting of fittings and brackets, cutting and making good the walls wherever required.					
1.3.2	17.10.2	Kitchen sink without drain board					
	17.10.2.1	610x510 mm bowl depth 200 mm	Each	280	4,154.60		
1.4	17.28	Providing & fixing PVC waste pipe for sink oncluding PVC waste fitting Complete					
	17.28.2	Flexible Pipe					
	17.28.2.1	32mm Dia	Each	282	71.21		

S.NO.	(DSR-2014)	DESCRIPTION	UNIT	QTY.	RATE	AMOUNT (RS)	
						DSR	NON DSR
1.5	17.70	Providing and fixing PTMT Bottle Trap for Wash basin and sink.					
	17.70.1	Bottle trap 31 mm single piece moulded with height of 270 mm, effective length of tail pipe 260 mm from the centre of the waste coupling 77 mm breadth with 25 mm minimum water seal, weighing not less than 260 gms.	Each	280	473.38		
1.6	17.72	Providing & fixing PTMT towel ring trapezoidal shape 215 mm long 200 mm wide with minimum distance of 37 mm from wall face with concealed fittings arrangement of approved quality and colour weighing not less than 88 gms	Each	280	209.00		
1.7	18.49	Providing and fixing C.P. brass bib cock of approved quality conforming to IS: 8931					
	18.49.1	15 mm nominal bore	Each	280	439.52		
1.8	18.51	Providing and fixing C.P. brass long body bib cock of approved quality conforming to IS standards and weighing not less than 690 gms.					
	18.51.1	15 mm nominal bore	Each	280	584.10		

S.NO.	(DSR-2014)	DESCRIPTION	UNIT	QTY.	RATE	AMOUNT (RS)	
						DSR	NON DSR
1.9	18.53	Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS 8931 a) 15 mm nominal bore.					
	18.53.1	15 mm nominal bore	Each	2000	485.63		
1.10	18.21	Providing and fixing uplasticised PVC connection pipe with brass unions :					
	18.21.2	45 cm length					
	18.21.2.1	15 mm nominal bore	Each	280	65.62		
1.11	17.80	Providing and fixing white vitreous china battery based infrared sensor operated urinal of approx. size 610 x 390 x 370 mm having pre & post flushing with water (250 ml & 500 ml consumption), having water inlet from back side, including fixing to wall with suitable brackets all as per manufacturers specification and direction of Engineer-in-charge.	Each	RO	15,997.78		
1.12	8.10	Providing and fixing stone slab with table rubbed, edges rounded and polished, of size 75x50 cm deep and 1.8 cm thick, fixed in urinal partitions by cutting a chase of appropriate width with chase cutter and embedding the stone in the chase with epoxy grout or with cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 6 mm nominal size) as per direction of Engineer-in-charge and finished smooth.					
	8.10.1	White Agaria Marble Stone	sqm	RO	3,121.61		
1.13	18.64	Providing & fixing PTMT swivelling shower, 15mm nominal bore. weighing not less than 40 gms.	Each	280	135.59		

S.NO.	(DSR-2014)	DESCRIPTION	UNIT	QTY.	RATE	AMOUNT (RS)	
						DSR	NON DSR
1.14	18.22	Providing and fixing C.P. brass shower rose with 15 or 20 mm inlet :					
	18.22.1	100 mm diameter	each	280	68.92		
1.15	18.63	Providing and fixing PTMT angle stop cock 15 mm nominal bore, weighing not less than 85 gms	Each	270	182.60		
1.16	M.R.	Supplying, storing, handling, shifting, installation, testing and commissioning of CP flexible hose, spray, wall flange etc. complete. ROCA make (Model -RF9060A1) or Equivalent.	Each	280	1563.50		

S.NO.	(DSR-2014)	DESCRIPTION	UNIT	QTY.	RATE	AMOUNT (RS)	
						DSR	NON DSR
1.17	MR	Providing and fixing straight type Macfit single body push fit type WC pan connector with factory supplied spring loaded seal guard of McAlpine, UK with integral single mould sealing fins made of flexible EVA body, including bush/adaptor for use with C.I. Pipe as supplied with the pan connector.	Each	280	176.00		
1.18	MR	Providing and fixing CP brass single lever low flow Sink mixer with 15 mm CP brass single lever pillar cock with pop up and waste complete including cutting and making good the walls where required. ROCA make (Model - RT5A3060C00) or Equivalent.	Each	280	2810.90		
		TOTAL FOR SUB HEAD - I CARRIED TO SUMMARY OF PRICES					
		SUBHEAD-II: DRAINAGE INSTALLATIONS					
2.1	10.16.1	Steel work in built up tubular (round, square or rectangular hollow tubes etc.) trusses etc., including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer, including welding and bolted with special shaped washers etc. complete	Kg.	345	98.43		
2.2	13.62.1	Painting steel work with synthetic enamel paint of approved brand and manufacture to give an even shade, two or more coats.	sqm	600	101.63		
2.3	17.35	Providing and fixing soil, waste & vent pipes					
	17.35.1	100 mm dia					
	17.35.1.2	Centrifugally cast (spun) iron socket & spigot (S&S) pipe as per IS: 3989	Rm	3950	877.85		
	17.35.2	75mm diameter :					
	17.35.2.2	Centrifugally cast (spun) iron socketed pipe as per IS: 3989	Rm	450	756.90		
2.4	17.37	Providing and fixing MS holder bat clamps of approved design to cast iron (spun) pipe embedded in and Including cement concrete blocks 10 x10 x10cm of 1:2:4 mix (1 cement : 2 coarse sand : 4 graded stone aggregate 20mm nominal size) including cost of cutting holes and making good the walls etc.					
	17.37.1	For 100mm dia. Pipe	Each	4500	146.25		
	17.37.2	For 75mm dia. Pipe	Each	250	144.05		

S.NO.	(DSR-2014)	DESCRIPTION	UNIT	QTY.	RATE	AMOUNT (RS)	
						DSR	NON DSR
2.5	17.39	Providing and fixing bend of required degree .					
	17.39.1	100mm					
	17.39.1.1	Sand cast iron S&S as per IS - 1729	Each	1000	415.61		
2.6	17.43	Providing and fixing single equal plain junction of reqd. degree with access door, insertion rubber washer 3mm thick, bolts and nuts complete.					
	17.43.1	100x100x100mm					
	17.43.1.2	Standerd cast (spun) iron pipe IS-3989	Each	850	596.68		
2.7	17.55.1.2	Providing and fixing door piece, insertion rubber washer 3mm thick, bolts and nuts complete, in 100mm Centrifugally cast (spun) iron pipe S&S as per IS-3989	Each	500	491.13		
2.8	17.56	Providing and fixing terminal guard 100mm standard cast (spun) iron S&S					
2.8.1	17.56.1	100 mm					
	17.56.1.2	Sand cast iron S&S as per IS - 3989	Each	65	415.61		
2.8.2	17.56.2	75 mm					
	17.56.2.2	Sand cast iron S&S as per IS - 3989	each	35	354.63		
2.9	17.58	Providing lead caulked joints to centrifugally cast (spun iron pipes and fittings of diametre.					
	17.58.1	100mm	Each	550	233.15		
	17.58.2	75 mm	Each	150	196.37		
2.10	17.60	Providing and fixing cast iron trap of self cleansing design with cast iron screwed down or hinged grating with or without vent arm complete, including cost of cutting and making good the walls and floors.					
	17.60.1.1	100 mm inlet and 100 mm outlet Sand cast iron S&S as per IS: 3989	Each	200	939.83		
2.11	17.65	Painting sand cast iron / centrifugally cast iron(spun) iron soil, waste and vent pipes and fittings with paint of any colour such as chocolate, grey or buff etc. over a coat of primer (of approval quality) for new work					
	17.65.1	100mm dia cast (spun) iron S&S pipe	Rm	850	36.97		
	17.65.2	75 mm diameter pipe	Rm	350	28.22		

S.NO.	(DSR-2014)	DESCRIPTION	UNIT	QTY.	RATE	AMOUNT (RS)	
						DSR	NON DSR
2.12	18.10	Providing and fixing G.I. Pipes complete with G.I. Fittings and clamps. including cutting and making good the walls etc. required for waste connection from W.B. , A.S.P., Sump Rising main etc. Complete.					
	18.10.4	32 mm nominal bore	Rm	750	328.28		
	18.10.5	40 mm nominal bore	Rm	650	407.14		
	18.10.6	50 mm nominal bore	Rm	650	504.28		
2.13	18.29	Supply pig lead at site of work.	quintal	35	10,009.52		
2.14	18.40	Painting G.I. pipes and fittings with two coats of anti-corrosive bitumastic paint of approved quality:					
	18.40.4	32 mm nominal bore	Rm	750	9.95		
	18.40.5	40 mm nominal bore	Rm	650	11.33		
	18.40.6	50 mm nominal bore	Rm	450	13.53		
2.15	18.58.1.2	Providing and fixing PTMT grating of approved quality, colour and make 125 mm nominal dia with 25 mm waste hole	Each	35	54.86		
2.16	18.66	Providing and laying flanged C.I. standard specials such as tees, bends, collars, tapers, caps. Etc., suitable for flanged jointing as per IS: 1538					
	18.66.1	Upto 300mm dia.	quintal	55	6,309.74		
2.17	19.2.1	Providing and laying cement concrete 1:5:10 (1 cement: 5 coarse sand: 10 graded stone aggregate 40 mm nominal size) around 100mm dia. SW / CI / waste pipes including bed concrete as per standard design	Rm	750	566.83		
2.18	12.41	Providing and fixing on wall face unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion, (i) Single socketed pipes.					
	12.41.2	110 mm diameter	metre	3200	221.58		

S.NO.	(DSR-2014)	DESCRIPTION	UNIT	QTY.	RATE	AMOUNT (RS)	
						DSR	NON DSR
2.19		Providing and fixing on wall face unplasticised - PVC moulded fittings/ accessories for unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS :5382, leaving 10 mm gap for thermal expansion.					
	12.42.5	Bend 87.5°					
	12.42.5.2	110 mm bend	Each	450	154.53		
	12.42.6	Shoe (Plain)					
	12.42.6.2	110 mm Shoe	Each	350	282.27		
2.20	12.43	Providing and fixing unplasticised -PVC pipe clips of approved design to unplasticised - PVC rain water pipes by means of 50x50x50 mm hard wood plugs, screwed with M.S. screws of required length, including cutting brick work and fixing in cement mortar 1:4 (1 cement : 4 coarse sand) and making good the wall etc. complete.					
	12.43.2	110 mm	Each	750	180.83		
2.21	12.22	Making khurras 45x45 cm with average minimum thickness of 5 cm cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate of 20 mm nominal size) over P.V.C. sheet 1 m x1 m x 400 micron, finished with 12 mm cement plaster 1:3 (1 cement : 3 coarse sand) and a coat of neat cement, rounding the edges and making and finishing the outlet complete.	Each	25	178.53		
2.23	M.R.	Providing and fixing G.I. Inlet fitting of suitable size with 2 & 3 Nos. G.I. Socket 32 & 40 welded G.I. pipe and dipped in hot bitumen complete in all respect.					
	M.R.	100 mm diameter pipe (Hopper)	Each	350	988.00		

S.NO.	(DSR-2014)	DESCRIPTION	UNIT	QTY.	RATE	AMOUNT (RS)	
						DSR	NON DSR
2.24	M.R	Providing and fixing floor drain made of 100 x 50 dia elbow / tee as applicable connected with 50 dia GI pipe painted with primer, two coats of black bituminastic paint,wrapping 1 mm thick PVC tape and final coat of black bituminastic paint B109 complete in all complete including cutting and making good the walls and floor wherever required	Each	350	993.00		
2.25	M.R.	Providing and fixing flanged cleanout plug with M.S. flanged tail pieces, blind flang, 6mm dia nut & bolts, gasket and washers fixed to C.I. Pipe with drip seal joint complete in all complete including cutting and making good the walls and floor wherever required					
	M.R.	with 100 mm dia. Pipe	Each	350	1,104.70		
2.26	M.R.	Providing & fixing of epoxy coated 25 mm thick C.I. Grating with frame for channel drains including all accessories complete					
	M.R.	350 wide	Rm	32	246.00		
		TOTAL FOR SUB HEAD - I CARRIED TO SUMMARY OF PRICES					
		SUBHEAD-III: WATER SUPPLY INSTALLATIONS					
3.1	10.2	Structural steel work riveted, bolted or welded in built up sections, trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete.	kg	150	70.73		
3.2	18.10	Providing and fixing G.I. pipes complete with GI fittings and clamps including cutting and making good the walls etc. (Exposed on wall)					
3.2.1	18.10.1	15 mm dia, nominal bore	Rm	3200	205.75		
3.2.2	18.10.2	20 mm dia, nominal bore	Rm	2200	238.46		
3.2.3	18.10.3	25 mm dia, nominal bore	Rm	2000	290.93		
3.2.4	18.10.4	32 mm dia, nominal bore	Rm	1800	328.28		
3.2.5	18.10.5	40 mm dia, nominal bore	Rm	1000	407.14		
3.2.6	18.10.6	50 mm dia, nominal bore	Rm	750	504.28		

S.NO.	(DSR-2014)	DESCRIPTION	UNIT	QTY.	RATE	AMOUNT (RS)	
						DSR	NON DSR
3.3	18.13.2	Making connection of GI distribution branch with GI main of 50-80mm nominal bore by providing and fixing tee, including cutting and threading the pipe etc. complete.	Item	22	728.01		
3.4	18.18.3	Providing & Fixing of Garden hydrant outlet consisting 1 No. 25mm dia. Ball valve,(Brass) for connecting rubber hose, pipes & fittings.	Each	300	430.39		
3.5	18.17	Providing and fixing of gun metal gate valve with CI wheel of approved quality (screwed ends)					
3.5.1	18.17.2	32 mm dia, nominal bore	Each	200	479.70		
3.5.2	18.17.3	40 mm dia, nominal bore	Each	50	560.04		
3.6	18.37	Constructing masonry Chamber 60x45x50 cm,inside with 75 class designation brick work in cement mortar 1:5 (1 cement:5 fine sand) for water meter complete with C.I. Doble flap surface box 400x200x200mm (inside) with locking arrangement and RCC top slab 1:2:4 mix (1 cement : 2 corase sand: 4 graded stonr aggregate 20mm nominal size) necessary excavation foundation concret 1:5:10 (1 cement:5 fine sand : 10 graded stone aggregate 40 mm nominal size) and inside plastering with cement mortor 1:3 (1 cement : 3 coarse sand) 12 mm thick finished with a floating coat of neat cement complete as per standard design					
	18.37.1	With F.P.S. bricks	Each	300	5,777.34		
3.7	18.40	Painting GI pipes and fittings with two coats of anti corrosive bitumastic paint of approved quality					
3.7.1	18.40.1	15 mm dia, nominal bore	Rm	2000	5.55		
3.7.2	18.40.2	20 mm dia, nominal bore	Rm	2800	6.55		
3.7.3	18.40.3	25 mm dia, nominal bore	Rm	2000	8.37		
3.7.4	18.40.4	32 mm dia, nominal bore	Rm	750	9.95		
3.7.5	18.40.5	40 mm dia, nominal bore	Rm	900	11.33		
3.8	18.41	Providing and filling sand of garding zone V or coraser grade all round the pipes in external work					
3.8.1	18.41.2	20 mm NB	Rm	150	64.37		
3.8.2	18.41.3	25 mm NB	Rm	175	66.05		

S.NO.	(DSR-2014)	DESCRIPTION	UNIT	QTY.	RATE	AMOUNT (RS)	
						DSR	NON DSR
3.9	18.46	Providing and fixing G.I. union in G.I. pipe including cutting and threading the pipe and making long screws etc. complete.					
3.9.1	18.46.1	15mm nominal bore	Each	150	158.07		
3.9.2	18.46.2	20mm nominal bore	Each	90	180.30		
3.9.3	18.46.3	25mm nominal bore	Each	90	191.40		
3.9.4	18.46.4	32mm nominal bore	Each	100	230.28		
3.10	18.49	Providing and fixing C.P. brass bib cock of approved quality confirming to IS:8931					
	18.49.1	15mm nominal bore	Each	40	439.52		
3.11	18.52	Providing and fixing C.P. brass stop cock (concealed) of standard design and of approved make conforming to IS:8931.					
	18.52.1	15 mm dia nominal bore	Each	20	592.80		
3.12	18.62	Provide and fixing PTMT ball cock of approved quality, colour and make complete with epoxy coated aluminium rod with L.P/H.P.H.D. plastic ball					
	18.62.5	50 mm dia NB, 242mm long. Weighing not less than 1240 gms.	Set	20	1,341.43		
3.13	18.18	Providing and fixing ball valve (brass) of approved quality, High or low pressure, with plastic floats complete :					
3.13.2	18.18.2	20 mm nominal bore	each	4	392.08		
3.13.2	18.18.3	25 mm nominal bore	each	4	430.39		

S.NO.	(DSR-2014)	DESCRIPTION	UNIT	QTY.	RATE	AMOUNT (RS)	
						DSR	NON DSR
3.14	19.19	Providing & fixing in position precast RCC manhole cover and frame of reqd. shape and approved quality.					
	19.19.4.1	Circular shape 560 internal dia.	Nos	8	1,584.67		
3.15	18.8	Providing and fixing chlorinated poly vinyl chloride (CPVC) pipes having thermal stability for hot & coldwater supply, including all CPVC plain & brass threaded fitting, including fixing the pipe with clamps at 1 m spacing. This includes jointing of pipes & fitting with one step CPVC solvent cement and cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge. (Concealed work including cutting chases and making good the walls etc.)					
3.15.1	18.8.1	15mm nominal outer dia. Pipes.	Metre	3000	258.26		
3.15.2	18.8.2	20mm nominal outer dia. Pipes.	Metre	1600	283.51		
3.15.3	18.8.3	25mm nominal outer dia. Pipes.	Metre	1600	336.03		
3.15.4	18.8.4	32mm nominal outer dia. Pipes.	Metre	1500	404.78		
3.16	18.12	Providing and fixing GI pipes complete with GI fittings including trenching and refilling etc. (External work)					
3.16.1	18.12.4	32 mm dia nominal bore	Metre	250	268.83		
3.16.2	18.12.6	50 mm	Metre	100	382.13		
3.16.3	18.12.8	80mm	Metre	65	609.35		
3.17	18.13	Making connection of GI distribution branch with GI main following sizes by providing and fixing tee, including cutting and threading the pipe etc, complete					
		Coupling/Socket					
3.17.1	18.13.2	50mm to 80mm nominal bore	Each	5	728.01		

S.NO.	(DSR-2014)	DESCRIPTION	UNIT	QTY.	RATE	AMOUNT (RS)	
						DSR	NON DSR
3.18	18.32.1	Constructing masonry chamber 30x30x50cm, inside with 75 class designation brick work in cement mortar 1:4 (1 cement : 4 coarse sand) for stop cock with C.I. Surface box 100x100x75 mm (inside) with hinged cover fixed in cement concrete slab 1:2:4 (1 cement:2 coarse sand:4 graded stone aggregate 20mm nominal size) necessary excavation foundation concrete 1:5:10 (1 cement:5 fine sand: 10 graded stone aggregate 40mm nominal size) and inside plastering with cement mortar 1:3 (1 cement : 3 coarse sand) 12mm thick finished with a floating coat of neat cement complete as per standard design with F.P.S. bricks.	Each	6	1,107.41		
3.19	M.R.	Providing and fixing insulation with thermaflex elastomeric nitrile rubber sheets complete with plastering of 20 mm thick insulation with thermaflex elastomeric nitrile rubber sheets for hot water & cold water pipes exposed to sun complete with plastering.					
3.19.1	M.R.	15 mm dia, nominal	Rm	750	176.00		
3.19.2	M.R.	20 mm dia, nominal	Rm	650	192.00		
3.19.3	M.R.	25 mm dia, nominal	Rm	500	218.60		
3.19.4	M.R.	32 mm dia, nominal	Rm	450	235.00		
3.19.5	M.R.	40 mm dia, nominal	Rm	500	254.00		
3.19.6	M.R.	50 mm dia, nominal	Rm	300	270.00		
3.19.7	M.R.	65 mm dia, nominal	Rm	300	295.00		
3.19.8	M.R.	80 mm dia, nominal	Rm	250	315.00		
3.20	M.R.	Providing and fixing brass automatic air vent at the top of each riser.					
		25mm diameter	Each	50	846.80		

S.NO.	(DSR-2014)	DESCRIPTION	UNIT	QTY.	RATE	AMOUNT (RS)	
						DSR	NON DSR
3.21		Providing and fixing pressure regulating station for cold water supply comprising of 3 nos gun metal ball valves on, inlet/outlet and bye-pass and 1 no. PRV unit (diaphragm type) with flanged connection, 2 nos pressure gauge on inlet and outlet, 1no 15 mm dia safety valve. The complete system is tested to a pressure not less than 3.0 kg/cm ² and suitable to reduce the pressure as desired including flanges/unions, nuts, bolts and washers complete as required for application. (horizontal or vertical as applicable).					
	M.R.	25mm dia.	Each	20	9724.00		
		TOTAL FOR SUB HEAD - I CARRIED TO SUMMARY OF PRICES					

S.NO.	(DSR-2014)	DESCRIPTION	UNIT	QTY.	RATE	AMOUNT (RS)	
						DSR	NON DSR
		EXTERNAL DRAINAGE INSTALLATION UPTO FIRST					
		SUBHEAD-IV: MANHOLE					
4.1	2.10	Excavating trenches of required width for pipe, cables etc including excavation for sockets ,& dressing of sides ,ramming of bottoms ,depth upto 1.5m including getting out the excavated soil,& then returning the soil as required, in layers not exceeding 20 cm in depth including consolidating each deposited layer by ramming ,watering, etc and disposing of surplus excavated soil as directed, within lead of 50m.					
		All kinds of soil					
	2.10.1.2	Pipes, cables etc exceeding 80 mm dia but not exceeding 300 mm dia	RM	75	199.54		
4.2	18.35	Constructing masonry Chamber 120x120x100 cm inside, in brick work in cement mortar 1:4 (1 cement : 4 coarse sand) for sluice valve, with C.I. surface box 100 mm. top diameter, 160 mm bottom diameter and 180 mm deep (inside) with chained lid and RCC top slab 1:2:4 mix (1 cement :2 coarse sand : 4 graded stone aggregate 20 mm nominal size) , i/c necessary excavation, foundation concrete 1:5:10 (1 cement : 5 fine sand:10 graded stone aggregate 40 mm nominal size) and inside plastering with cement mortar 1:3 (1 cement : 3 coarse sand) 12 mm thick finished with a floating coat of neat cement complete as per standard design :					
	18.35.1	With common burnt clay F.P.S.(non modular) bricks of class designation 7.5.	Each	20	15,395.31		
4.3	19.1	Providing laying and jointing glazed stoneware pipes grade Aqwith stiff mixture of cement mortar in the proportion of 1:1 (1 cement : 1 fine sand) including testing of joints etc. complete.					
4.3.1	19.1.2	150 mm diameter	Rm	35	300.68		
4.3.2	19.1.4	250 mm diameter	Rm	35	666.22		
4.4	19.2	Providing and laying cement concrete 1:5:10 (1 cement : 5 coarse sand : 10 graded stone aggregate 40 mm nominal size) around SW pipes including bed concrete as per standard design.					
4.4.1	19.2.2	150 mm diameter	Mtr	35	693.19		
4.4.2	19.2.4	250 mm diameter	Rm	20	934.52		

S.NO.	(DSR-2014)	DESCRIPTION	UNIT	QTY.	RATE	AMOUNT (RS)	
						DSR	NON DSR
4.5	19.4	Providing and fixing square mouth SW gully trap grade Ac complete CI grating brick masonry chamber with bricks of class designation 75 and water tight CI cover with frame of 300 x 300 mm size (inside) the weight of cover to be not less than 13.00 kg and frame to be not less than 5 kg. as per standard design. (COVER MIN. 4.5 KG & FRAME MIN.2.7 KG)					
4.5.2	19.4.3.1	180x150mm size P type With FPS bricks	Each	10	1,605.86		
4.6	19.6	Providing and laying non-pressure NP2 class (light duty) RCC pipes with collars jointed with stiff mixture of cement mortar in the proportion of 1:2 (1 cement : 2 fine sand) including testing of joints etc. complete.					
4.6.1	19.6.2	150 mm dia RCC pipe	Rm	35	333.16		
4.6.2	19.6.3	250 mm dia RCC pipe	Rm	40	448.23		
4.7	4.1	Providing and laying in position cement concrete of grade excluding the cost of centering and shuttering - all work up to plinth level					
	4.1.10	1:5:10 (1 cement : 5 coarse sand : 10 graded stone aggregate 40 mm nominal size)	cum	20	3,829.91		
4.8	19.7	Construction brick masonry manhole in cement mortar 1:4 (1cement : 4coarse sand) RCC top slab with 1:2:4 mix 9 with 75 class designation bricks in cement mortar 1:4 (1 cement : 4 coarse sand) RCC top slab with 1:2:4 mix (1 cement : 2 coarse sand 4 graded stone aggregate 20mm nominal size) foundation concrete 1:4:8 mix (1 cement : 4 coarse sand : 8 graded stone aggregate 40 mm nominal size) inside plastering 12 mm thick with cement mortar 1:3 (1 cement : 3 coarse sand) finished with floating coat of neat cement and making channels in cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size) finished with a floating coat of neat cement complete as per standard design.					
4.8.1	19.7.1.1	Inside size 90 x 80 cm and 45 cm deep including CI cover with frame (light duty) 455 x 610mm internal dimensions total weight of cover and frame to be not less than 38 Kg. (weight of cover 23 Kg. and weight of frame 15 Kg.), with FPS bricks with class designation 7.5	Each	4	8,137.13		
4.8.2	19.7.2.1	Inside size 120 x 90 cm and 90 cm deep including CI cover with frame (heavy duty) 500mm internal dia. Total weight of cover and frame to be not less than 116 Kg. (weight of cover to be 58 Kg. and weight of frame 58 Kg.)with FPS bricks class designation 75. (Sewerage Line)	Each	5	17,508.60		
4.9	19.8	Extra for depth for manholes					

S.NO.	(DSR-2014)	DESCRIPTION	UNIT	QTY.	RATE	AMOUNT (RS)	
						DSR	NON DSR
4.9.1	19.8.1.1	Size 90 x 80 cm with FPS bricks designation 7.5	M	2	5,393.06		
4.9.2	19.8.2.1	Size 120 x 90 cm with FPS bricks designation 7.5	M	2	6,460.01		
4.10	19.11	Constructing brick masonry circular manhole 1.22m internal dia at bottom and 0.56m dia at top in cement mortar 1:4 (1 cement : 4 coarse sand) inside cement plaster 12mm thick with cement mortar 1:3 (1 cement : 3 coarse sand) finished with a floating coat of neat cement, foundation concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm nominal size) and making necessary channel in cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20mm nominal size) finished with a floating coat of neat cement all complete as per standard design.					
	19.11.1	1.68m deep with SFRC cover and frame (heavy duty HD-20 grade designation) 560mm internal diameter conforming to I.S. 12592, total weight of cover and frame to be not less than 182 kg. fixed in cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20mm nominal size) including centering shuttering all complete. Excavation, foot rests and 12mm thick cement plaster at the external surface shall be paid for seperately).					
	19.11.1.1	With F.P.S. bricks class designation 7.5	Each	3	15,751.90		
4.11	19.12	Extra for depth for circular manholes 1.22m internal dia (at bottom) with beyond 1.68m to 2.29m.					
	19.12.1	With F.P.S. bricks class designation 7.5	Each	3	5,998.06		

S.NO.	(DSR-2014)	DESCRIPTION	UNIT	QTY.	RATE	AMOUNT (RS)	
						DSR	NON DSR
4.12	19.16	Providing orange colour safety foot rest of minimum 6 mm thick plastic encapsulated as per IS: 10910 on 12 mm dia steel bar conforming to IS: 1786 having minimum cross section as 23 mm x 25 mm and over all minimum length 263 mm and width as 165 mm with minimum 112 mm space between protruded legs having 2 mm tread on top surface by ribbing or chequering besides necessary and adequate anchoring projections on tail length on 138 mm as per standard drawing and suitable to with stand the bend test and chemical resistance test as per specification and having manufacture's permanent identification mark to be visible even after fixing, including fixing in manholes with 30x20x15cm cement concrete block 1:3:6 (1 cement : 3 coarse sand :6 graded stone aggregate 20 mm nominal size) complete as per design.	Each	5	298.05		

S.NO.	(DSR-2014)	DESCRIPTION	UNIT	QTY.	RATE	AMOUNT (RS)	
						DSR	NON DSR
4.13	19.27.1	Constructing brick masonry road gully chamber 50x45x60 cm with bricks of class designation 75 in cement mortar 1:5 (1 cement : 5 fine sand) including 500 x 450 mm (heavy duty) precast RCC horizontal grating with frame complete as per standard design: with FPS bricks	Each	10	3,785.43		
4.14	19.21.1	Making connection of drain or sewer line with existing manhole including breaking into and making good the walls, floors with cement cincrete 1:2:4 mix (1cement: 2 coarse sand : 4 graded stone aggregate 20mm nominal size) cement plastered on both sides with cement mortar 1:3 (1cement : 3 coarse sand) finished with a floating coat of neat cement and making necessary channels for the drain etc. complete for pipes 100 to 250mm dia.	Item	1	349.45		
		TOTAL FOR SUB HEAD - I CARRIED TO SUMMARY OF PRICES					